

Serial No. 09/765,85.

In the claims

1.(currently amended) A method of reducing calculations in the decoding of a M-ary modulated convolutionally coded signal in a radio communication system, the method comprising the steps of:

- a) determining a single function for a soft-decision metric for each bit in a symbol by restricting ~~the a~~ set of all possible Gray-coded constellation points to those closest to a boundary between a bit value of 0 and 1 for each bit in ~~the~~ an input symbol and applying a predetermined function corresponding to ~~the a~~ range of restricted constellation points to ~~the an~~ entire possible range of symbols;
- b) inputting ~~a~~ <sup>the</sup> symbol having real part,  $x$ , and an imaginary part,  $y$ ;
- c) setting ~~a the~~ soft-decision metric for each bit in the symbol using the predetermined function from the determining step;
- d) outputting the soft-decision metrics for each bit of the symbol to a turbo decoder;
- e) decoding the symbol in the turbo decoder; and
- f) repeating steps a) through e) until all symbols to be input are decoded.

2. (original) The method of claim 1, wherein the setting step includes a substep of scaling the soft-decision metrics.

3. (currently amended) The method of claim 2, wherein the scaling substep includes scaling the soft-decision metrics by a factor of  $\beta A_d / A_p$ , wherein  $\beta$  is the squared magnitude of a filtered pilot signal, and  $A_d$  and  $A_p$  are the data and pilot signal gains, respectively.

4. (currently amended) The method of claim 1, wherein the predetermined function of the determining step is defined by the difference between the squares of the distances between the set of all possible Gray-coded restricted constellation points

Serial No. 09/765,851

having 0 and 1 bit values and a hypothetical symbol falling within the range of restricted constellation points.

5.(Cancelled)

6.(currently amended) The method of claim 8, wherein the inputting step includes phase shifting the symbol by  $e^{j\pi/4}$ .

7. (Cancelled)

8.(Currently Amended) A method of reducing calculations in the decoding of an 8-PSK modulated convolutionally coded signal in a radio communication system, the method comprising the steps of:

- a) providing a set of eight possible Gray-coded symbols for the 8-PSK modulated convolutionally coded signal in a constellation;
  - b) defining radial boundaries in ~~the~~<sup>the</sup> constellation ~~bisecting the points in the~~<sup>the</sup> constellation;
  - c) inputting a symbol ~~having real part, x, and an imaginary part, y;~~
  - d) plotting the location of the symbol in the constellation;
  - e) locating ~~the~~ two nearest constellation points to the symbol having a 0 value and a 1 value for each bit;
  - f) setting a soft-decision metric for each bit using the two nearest constellation points from the locating step;
  - g) outputting ~~the~~<sup>the</sup> soft-decision metrics ~~for each bit of the symbol to a turbo decoder;~~
  - h) decoding the symbol in the turbo decoder;
  - i) repeating steps a) through h) until all symbols to be input are decoded;
- wherein ~~after the setting steps, further comprising~~<sup>the setting steps, further comprising</sup> the step of scaling the soft-decision metrics; and
- wherein the scaling step includes scaling the soft-decision metrics by a factor of  $\beta A_d / A_p$ , wherein  $\beta$  is ~~the~~<sup>a</sup> squared magnitude of a filtered pilot signal, and  $A_d$  and  $A_p$  are ~~the~~ data and pilot signal gains, respectively.

Serial No. 09/765,85,

9. (original) A method of reducing calculations in the decoding of an 8-PSK modulated convolutionally coded signal in a radio communication system, the method comprising the steps of:

- a) inputting a symbol having real part,  $x$ , and an imaginary part,  $y$ ;
- b) setting a soft-decision metric of ~~the~~ <sup>$a$</sup>  first bit of the symbol equal to the value of the imaginary part,  $y$ , of the symbol;
- c) setting a soft-decision metric of ~~the~~ <sup>$a$</sup>  second bit of the symbol equal to the value of the real part,  $x$ , of the symbol;
- d) setting a soft-decision metric of ~~the~~ <sup>$a$</sup>  third bit of the symbol equal to  $(|x| - |y|) \cdot \frac{1}{\sqrt{2}}$
- e) outputting the soft-decision metrics <sup>of the first, second and third bits</sup> ~~for each bit~~ of the symbol to a turbo decoder;
- f) decoding the symbol in the turbo decoder; and
- g) repeating steps a) through f) until all symbols to be input are decoded.

10. (currently amended) The method of claim 9, wherein the inputting step includes phase shifting the symbol by  $e^{j\pi/8}$ .